


PESO EXATO
balanças

LOAD CELL
TYPE PE TYPE I

CAPACITY:
250 TO 2000KG



Kg	A	B	C	D	E	F	G	D1	D2	D3
250kg	130	32	50.5	32	12.63	76.2	25.4	Ø 13	M12	Ø 13.5

COMPATIBLE BTBI/TYPE I
FOOT: M12



LOAD CELL CALIBRATION CERTIFICATE

MODEL	250-2000kg
PRECISION CLASS	C3
CABLE LENGTH	10 M
OUTPUT SIGNAL	2.0 0.01 mV/V
ZERO OUTPUT SIGNAL	<1% of R.O.
REPEATABILITY ERROR	<0.020 % of R.O.
CREEP (30 MIN).	<0.025 % of R.O.
TEMPERATURE EFFECT ON ZERO	<0.020 % of R.O.
INPUT IMPEDANCE	385.0 Ω
OUTPUT IMPEDANCE	350.2 Ω
INSULATION IMPEDANCE	≥5000 MΩ
MAXIMUM INPUT VOLTAGE	15V
NOMINAL TEMPERATURE RANGE	-10...+40 °C
OPERATING TEMPERATURE RANGE	-30...+70 °C

WIRING DIAGRAM

